AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions and listings of claims in the application:

- 1. (Withdrawn) A dummy apparatus for a test or inspection for a vehicle collision prediction apparatus or a component thereof, wherein a dummy object having less reflection of electric wave is covered with a cloth, and the cloth is swayed.
- 2. (Withdrawn) A dummy apparatus according to claim 1, wherein the cloth is swayed by a blower that sends air toward the dummy object.
- 3. (Withdrawn) A dummy apparatus according to claim 1, wherein the dummy object is vibrated by a vibrating apparatus attached to the dummy object for swaying the cloth.
- 4. (Withdrawn) A dummy apparatus according to claim 1, wherein the dummy object is moved by a moving apparatus attached to the dummy object for swaying the cloth.
- 5. (Withdrawn) A dummy apparatus according to claim 1, wherein the dummy object is hung down.

Application No. 10/593,616 Attorney Docket No. 08295.0004-00000

6. (Withdrawn) A dummy apparatus according to claim 1, wherein the dummy object is formed into a human, and the cloth is clothing.

7. (Cancelled)

- 8. (Currently Amended) A <u>The dummy testing</u> apparatus according to claim [[7]] 18, wherein plural reflection plates are provided attached to the dummy object.
- 9. (Currently Amended) A The dummy testing apparatus according to claim [[7]] 18, wherein a drive means for displacing the reflection plate relative to the collision-prediction apparatus radar is attached to the dummy object.
- 10. (Currently Amended) A <u>The dummy testing</u> apparatus according to claim [[7]] <u>18</u>, wherein an area changing apparatus for changing the <u>a</u> reflection area of the reflection plate with time is attached to the dummy object.
- 11. (Currently Amended) A <u>The dummy testing</u> apparatus according to claim [[7]] 18, wherein the reflection plate is deformable, and a drive apparatus for deforming the reflection plate is attached to the dummy object.
- 12. (Currently Amended) A <u>The dummy testing</u> apparatus according to claim [[7]] 18, wherein the dummy object is formed into has a generally human shape.

- 13. (Currently Amended) A <u>The dummy testing</u> apparatus according to claim [[7]] 18, wherein the dummy object is covered with a cloth.
- 14. (Withdrawn) A test method for testing a vehicle collision prediction apparatus or a component thereof wherein a dummy object having less reflection of electric wave is covered with a cloth and the cloth is swayed.
- 15. (Currently Amended) A test method for testing a vehicle collision prediction apparatus or a component thereof by using a dummy testing apparatus having a dummy object having less reflection of electric wave and a reflection plate, which reflects a millimeter wave, attached to the dummy object comprising:

mounting a radar on a vehicle; and

providing a dummy object spaced away from the radar, with a reflection plate attached to the dummy object;

wherein the reflection plate has a first amount of reflection, and the dummy object has a second amount of reflection,

and wherein the second amount of reflection is less than the first amount of reflection.

16. (Cancelled)

17. (Currently Amended) A <u>The</u> test method according to claim 15, wherein the <u>a</u> reflection area of the reflection plate is changed with time.

18. (New) A testing apparatus for a vehicle collision prediction apparatus, comprising:

a radar mounted on a vehicle;

a dummy object spaced away from the radar; and

a reflection plate attached to the dummy object,

wherein the reflection plate has a first amount of reflection, and the dummy object has a second amount of reflection,

and wherein the second amount of reflection is less than the first amount of reflection.